



TT Industrial Packaging is a



Talu
Trade
Group

Company.

INDEX

- Composite Straps
- Hotmelt Straps / Baling Straps
- Woven Straps
- Lashing Straps and Ladder Buckles
- Wire Buckles
- Coil Dispensers
- PET Straps
- PP Straps
- Dunnage Bags
- Stretch Films
- Accessories



TT ENDÜSTRİYEL AMBALAJ MAKİNA SAN. ve TİC. A.Ş.

Factory Address: Velimese Organize Sanayi Bolgesi Mahallesi 227. Sok.,3/1 Ergene TEKIRDAG / TURKEY
Tel: +90 282 674 33 23 Fax: +90 282 674 33 25

CO-STRAP Verpackungslosungen GmbH

Company Address: 91541 Rothendurg ob der Tauber, Germany
Warehouse Address: Marie-Curie-Str. 5 , 63526 Erlensee, Germany

www.co-strap.com



Composite Straps



Printed Composite Straps
 Ultraflex Quality
 Strapping Kits
 Colored Corded Straps



CO-STRAP Composite Corded Straps are produced from high tenacity polyester yarns and polypropylene flakes. Composite straps are stiff but flexible products that can be easily used at various packaging applications. They are highly resistant to severe weather conditions (especially hot climates) and unlike PET and Steel Straps they do not break instantly from a single point against impacts. Based on the application types and packaging volume they can be much more economical than other strap types.

- High Strength
- Shock Absorbent
- Does not get loose (High retain tension)
- Highly Elastic and Flexible
- No sharp edges that could damage your products
- Does not damage cargo
- Resistant to Severe Weather Conditions and UV
- Cost Effective
- Light-Weight
- Rust-proof, doesn't rust or corrode
- Resistant to chemicals
- Fast and easy to use
- Safe Usage
- Flex / Ultraflex Composite Straps can be feed easily through the buckle
- Printing with company name and/or logo on the straps is available
- Germanischer Lloyd approved



POLYESTER COMPOSITE STRAPS

| CO-STRAP Product Code | Width (mm) | Linear Break Strength (daN) | Coil Length* (m) | Core Diameter (mm) |
|---------------------------------|------------|-----------------------------|------------------|--------------------|
| LIGHT APPLICATION | | | | |
| CS13L (CC-40/2) | 13 | 240 | 1100 | 200 |
| CS16L (CC-50/2) | 16 | 310 | 850 | 200 |
| CS19L (CC-60/2) | 19 | 330 | 600 | 200 |
| CS25L | 25 | 440 | 500 | 200 |
| STANDARD APPLICATION | | | | |
| CS13ST (CC-40) | 13 | 340 | 1100 | 200 |
| CS16ST (CC-50) | 16 | 450 | 850 | 200 |
| CS19ST (CC-60) | 19 | 510 | 600 | 200 |
| CS25ST | 25 | 690 | 400 / 500 | 200 |
| STRONG APPLICATION | | | | |
| CS16STR (CC-55) | 16 | 540 | 750 / 600 | 200 |
| CS19STR (CC-65) | 19 | 600 | 650 / 500 | 200 |
| CS25STR (CC-85) | 25 | 800 | 500 | 200 |
| CS32STR (CC-105/6L) | 32 | 1150 | 300 | 406/200 |
| CS34STR (CC-105/6) | 34 | 1400 | 400 / 300 | 406/200 |
| EXTRA STRONG APPLICATION | | | | |
| CS19ESTR - ULTRAFLEX (CC-69) | 19 | 850 | 500 | 406/200 |
| CS25ESTR - ULTRAFLEX (CC-86UF) | 25 | 1050 | 500 / 450 | 406/200 |
| CS26ESTR - ULTRAFLEX (CC-89UF) | 26 | 1350 | 400 | 406/200 |
| CS32ESTR - ULTRAFLEX (CC-105UF) | 32 | 1650 | 300 | 406/200 |
| CS40ESTR - ULTRAFLEX (CC-150UF) | 40 | 2450 | 220 | 406/200 |



Textile Hotmelt Straps



- Printed Textile Straps
- Bale Press Strapping
- Dispenser Box Set
- Strapping Kits
- Colored Corded Straps



CO-STRAP Textile Corded Straps are produced from high tenacity polyester yarns and hotmelt Textile straps can be a good alternative for Steel and PET straps especially at cold and humid climates. Textile straps are soft products that can be used without buckles and is a cost effective alternative for PET and Steel straps which can only be used with battery charged tools or semi/full automatic strapping machines.

- High Strength
- Shock Absorbent
- Does not get loose (High retain tension)
- Highly Elastic and Flexible
- No sharp edges that could damage your products
- Does not damage cargo
- Resistant to Severe Weather Conditions and UV
- Cost Effective
- Light-Weight
- Fast and east to use
- Soft and can be used without buckle
- Printing with company name and/or logo on the straps is available
- Germanischer Llyod approved

POLYESTER TEXTILE (HOTMELT) STRAPS

| CO-STRAP Product Code | Width (mm) | Linear Break Strength (daN) | Coil Length* (m) | Core Diameter (mm) |
|---------------------------------|------------|-----------------------------|------------------|--------------------|
| BALE PRESS | | | | |
| WG9STBL (30WG BL) | 9 | 280 | 250 / 500 | 62 |
| WG13STBL (40WG BL) | 13 | 380 | 250 / 350 / 500 | 62 |
| WG16STBL (50WG BL) | 16 | 450 | 400 / 425 | 62 |
| LIGHT APPLICATION | | | | |
| WG9L (30WGL) | 9 | 230 | 1800 | 76 |
| WG13L (40WGL) | 13 | 330 | 1500 / 1100 | 76 |
| WG16L (50WGL) | 16 | 380 | 1200 / 850 | 76 |
| WG19L (60WGL) | 19 | 500 | 600 | 76 |
| STANDARD APPLICATION | | | | |
| WG9ST (30WG) | 9 | 280 | 1500 | 76 |
| WG13ST (40WG) | 13 | 380 | 1100 | 76 |
| WG16ST (50WG) | 16 | 450 | 850 | 76 |
| WG19ST (60WG) | 19 | 550 | 600 | 76 |
| STRONG APPLICATION | | | | |
| WG13STR (45WG) | 13 | 550 | 850 | 76 |
| WG16STR (55WG) | 16 | 600 | 600 | 76 |
| WG19STR (65WG) | 19 | 725 | 500 | 76 |
| WG25STR (85WG) | 25 | 950 | 500 | 76 |
| WG30STR (95WG) | 30 | 1200 | 150 | 76 |
| WG35STR (105 or 105/4WG) | 35 | 1400 | 150 | 76 |
| EXTRA STRONG APPLICATION | | | | |
| WG19ESTR (69WG) | 19 | 950 | 400 | 76 |
| WG25ESTR (86WG) | 25 | 1250 | 400 | 76 |
| WG38ESTR (150WG) | 38 | 2000 | 100 | 76 |

* : Different coil lengths are available upon request

* : Printed straps are available upon request



Woven Straps

Woven straps is an alternative to steel banding. Woven cord strapping has similar physical properties with textile straps. They have to be used with phosphated buckle.



| Woven Straps | | | | |
|---------------------------------|------------|-----------------------------|------------------|--------------------|
| CO-STRAP Product Code | Width (mm) | Linear Break Strength (daN) | Coil Length* (m) | Core Diameter (mm) |
| Standard Application | | | | |
| WV13ST | 13 | 360 | 1100 | 76 |
| WV16ST | 16 | 500 | 850 | 76 |
| WV19ST | 19 | 580 | 600 | 76 |
| Strong Application | | | | |
| WV13STR | 13 | 475 | 850 | 76 |
| WV16STR | 16 | 600 | 600 | 76 |
| WV19STR | 19 | 750 | 500 | 76 |
| WV25STR | 25 | 1000 | 500 | 76 |
| Extra Strong Application | | | | |
| WV19ESTR | 19 | 1100 | 400/500 | 76 |
| WV19ESTX | 19 | 1225 | 400/500 | 76 |
| WV25ESTR | 25 | 1400 | 300 | 76 |
| WV32ESTR | 32 | 1500 | 300 | 76 |

* : Different coil lengths are available upon request






Lashing



TT Industrial Packaging Company supplies all kinds of Lashing products and equipment as well as consultancy services on appropriate application ways with the help of its experts. Lashing products are designed to bear optimized specifications for cargo securing on land, marine and airline transportation, flat-racks, railcars & ships.

Cost effective • Re-stretchable • No product damage • Shock absorbent • Weather resistant • High retained tension • Light-weight portable • Does not rust out



| Lashing | | | |
|-----------------------|------------|-----------------------------|------------------|
| CO-STRAP Product Code | Width (mm) | Linear Break Strength (daN) | Coil Length* (m) |
| COLASH 100 | 25 | 2200 | 400 |
| COLASH 105 | 32 | 2000 | 250 |
| COLASH 105 S | 32 | 2300 | 250 |
| COLASH 150-AAR | 38 | 3500 | 200 |
| COLASH 200-AAR | 40 | 5000 | 200 |
| COLASH 500 | 50 | 5000 | 150 |
| COLABH 600 | 50 | 6000 | 150 |
| COLASH 750-AAR | 50 | 7500 | 150 |



Strapping Buckles



Strapping Buckles:

The thickness of the strapping buckles range from 8 mm to 40 mm and they are convenient to use in all types of strapping.

- Galvanized Buckles
- Phosphated Buckles



| Galvanized Wire Buckles | | | |
|-------------------------|------------|--------|------------------------|
| CO-STRAP Product Code | Width (mm) | Wire Ø | Quantity Per Box (pcs) |
| COB4G13 | 13 | 3.0 | 1000 |
| COB4G13-STD | 13 | 3.3 | 1000 |
| COB5G16 | 16 | 3.3 | 1000 |
| COB5G16-HD | 16 | 3.5 | 1000 |
| COB6G19 | 19 | 3.5 | 1000 |
| COB6G19-HD | 19 | 4.0 | 1000 |
| COB8G25 | 25 | 5.0 | 500 |
| COB8G25-HD | 25 | 6.0 | 400 |
| COB10G32 | 32 | 7.0 | 250 |
| COB12G40 | 38 | 7.0 | 200 |



| Phosphated Wire Buckles | | | |
|-------------------------|------------|--------|------------------------|
| CO-STRAP Product Code | Width (mm) | Wire Ø | Quantity Per Box (pcs) |
| COB4P13 | 13 | 3.0 | 1000 |
| COB4P13-STD | 13 | 3.3 | 1000 |
| COB5P16 | 16 | 3.3 | 1000 |
| COB5P16-HD | 16 | 3.5 | 1000 |
| COB6P19 | 19 | 3.5 | 1000 |
| COB6P19-HD | 19 | 4.0 | 1000 |
| COB8P25 | 25 | 5.0 | 500 |
| COB8P25-HD | 25 | 6.0 | 400 |
| COB10P32 | 32 | 7.0 | 250 |
| COB12P40 | 38 | 7.0 | 200 |





Coil Dispensers

CO-DISP101 Hotmelt and Woven Strap Dispenser

- Core size(mm) : 76
- Max. strap width(mm) : 38
- Max. face coil(mm) : 200
- Coil winding : O
- Wheel type : No wheel
- Assembled : Semi
- **Coil winding : R means Ribbon coil.
O means Oscillated/Mill Wound coil.

CO-DISP102 Hotmelt and Woven Strap Dispenser

- Core size(mm) : 76
- Max. strap width(mm) : 38
- Max. face coil(mm) : 260
- Coil winding : O
- Wheel type : 6" Plastic
- Assembled : Semi
- **Coil winding : R means Ribbon coil.
O means Oscillated/Mill Wound coil.

CO-DISP103 UNI Universal PET & PP & Composite Strap Dispenser

- Core size(mm) : 150, 200, 280 and 400
- Max. strap width(mm) : 65
- Max. face coil(mm) : 330
- Disc outer dia (mm) : Max. 600
- Coil winding : O
- Wheel type : 6" Rubber with steel center
- Assembled : Semi
- **Coil winding : R means Ribbon coil.
O means Oscillated/Mill Wound coil.

CO-DISP104 Composite Strap and PP Strap Dispenser

- Core size(mm) : 200
- Max. strap width(mm) : 40
- Max. face coil(mm) : 300
- Disc outer dia (mm) : Max. 450
- Coil winding : O
- Wheel type : 6" Plastic
- Assembled : Semi
- **Coil winding : R means Ribbon coil.
O means Oscillated/Mill Wound coil.


CO-DISP105-UNI Universal Composite Strap, PET Strap, Steel Strap and PP Strap Dispenser

- Core size(mm) : 400
- Max. strap width(mm) : 32
- Max. face coil(mm) : 260
- Disc outer dia (mm) : Max. 650
- Coil winding : R/O
- Wheel type : 8" Rubber with steel center
- Assembled : Semi
- **Coil winding : R means Ribbon coil.
O means Oscillated/Mill Wound coil.





PET Straps



PET Straps can be used in fully automatic pallet strapping machines during the packaging of products which require medium and high strength strapping. They can also be used by pneumatic strapping machines or battery powered strapping machines.

High breaking strength • Shock absorbent • Long term Elasticity • Resistant to severe weather conditions • No cargo damage • Don't get loose • Safe and fast usage

PET Straps

| CO-STRAP Product Type | Size (mm) | Linear Break Strength (daN) | Length (m) | Color | Surface |
|---------------------------|------------|-----------------------------|------------|-------|-----------|
| POLYESTER (PET) STRAP | 12x0.70 | 340 | 2500 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 15x0.70 | 380 | 1400 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 15.50x0.90 | 530 | 1500 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 16x0.60 | 345 | 1700 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 16x0.70 | 470 | 1550 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 16x0.70 | 470 | 1750 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 19x0.80 | 550 | 1200 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 19x1.00 | 700 | 1000 | Green | EMBOSSSED |
| POLYESTER (PET) STRAP | 12x0.60 | 280 | 2200 | Green | SMOOTH |
| POLYESTER (PET) STRAP | 15.50x0.90 | 630 | 1500 | Green | SMOOTH |
| POLYESTER (PET) STRAP | 19x1.00 | 840 | 1000 | Green | SMOOTH |
| POLYESTER (PET) STRAP | 19x1.27 | 1050 | 730 | Green | SMOOTH |
| POLYESTER (PET) STRAP | 19x1.27 | 1050 | 2200 | Green | SMOOTH |
| POLYESTER (PET) STRAP-ECO | 12x0.60 | 220 | 2200 | Green | EMBOSSSED |



PP Straps



PP Straps offer one of the most cost effective alternatives for light weight applications with low tensile strength. They can be used with buckles and welding system.

Safe and quick • No cargo damage • Cost effective • Medium resistance to severe weather conditions

PP Straps

| CO-STRAP Product Type | Type | Color | Size (mm) | Core (mm) | Coil Length (m) |
|--------------------------|-----------|-------|-----------|-----------|-----------------|
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 8x0.60 | 200x150 | 4000 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 12x0.60 | 200x150 | 3000 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 12x0.80 | 400x150 | 2000 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 8x0.60 | 200x150 | 4000 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 10x0.60 | 200x150 | 3500 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 12x0.60 | 200x150 | 3000 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | WHITE | 12x0.80 | 400x150 | 2000 |
| POLYPROPYLENE (PP) STRAP | MANUAL | WHITE | 16x0.80 | 400x150 | 1500 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | BLACK | 10x0.60 | 200x150 | 3500 |
| POLYPROPYLENE (PP) STRAP | AUTOMATIC | BLACK | 12x0.60 | 200x150 | 3000 |
| POLYPROPYLENE (PP) STRAP | MANUAL | BLACK | 16x0.80 | 400x150 | 1500 |




Dunnage Bags



Dunnage Bags provide the most cost-effective solutions to secure and stabilize the cargo inside the container, railway wagon or truck.

Dunnage bags ensure you that freight arrives at the final destination without any damage.

During long sea and railway shipments, it is necessary to fix the pallets in the container to prevent rubbing with each other, to eliminate the risk of overturning, etc.



There are two kinds of Dunnage bags: Polypropylene Woven and Kraft Paper.

The sizes and dimensions vary according to the weight of the pallets, the dimensions and the internal dimensions of the container.

At the same time, there are classifications which are called Levels in terms of quality (strength) of Dunnage Bags.



- Kraft Paper Dunnage Bags
- Polypropylene Woven Dunnage Bags
- Inflation Devices

ECO LINE LEVEL 1, LEVEL 2, LEVEL 3, LEVEL 4, LEVEL 5, DUNNAGE AIR BAG DIMENSIONS

| Dimension (inch) | Dimension (cm) |
|------------------|----------------|
| 24" x 36" | 61 x 91 |
| 36" x 48" | 91 x 122 |
| 36" x 72" | 91 x 183 |
| 48" x 72" | 122 x 183 |
| 48" x 84" | 122 x 213 |

* : Other Dimensions are also available upon request



Stretch Films



Prestretch Films reduce the amount of material required by as much as 50% for greater savings. A reel of Prestretch Film bobbins weight up to 70% less than a traditional 300 meters manual reel and makes packaging easier. More protection for delicate products thanks to a more delicate application of the film on pallet.

Economic • More light • More output • More strength • More protection • More resistance to impact and tearing • More safety • Reduced cost for waste material



Stretch Films

HP - HIGH PERFORMANCE STRETCH FILMS - AUTOMATIC USE

| Width (mm) | Gauge (my) | Length (m) | Gross Roll Weight (kg) | Core Weight (kg) | Net Roll Weight (kg) | Rolls Per Pallet |
|------------|------------|------------|------------------------|------------------|----------------------|------------------|
| 500 | 12 | 3,000 | 17.56 | 1.00 | 16.56 | 30 |
| 500 | 15 | 2,400 | 17.56 | 1.00 | 16.56 | 30 |
| 500 | 17 | 2,100 | 17.42 | 1.00 | 16.42 | 30 |
| 500 | 20 | 1,800 | 17.56 | 1.00 | 16.56 | 30 |
| 500 | 23 | 1,550 | 17.40 | 1.00 | 16.40 | 30 |

PIU PRESTRETCH FILMS - HAND USE

| Width (mm) | Gauge (my) | Length (m) | Gross Roll Weight (kg) | Core Weight (kg) | Net Roll Weight (kg) | Rolls Per Pallet |
|------------|------------|------------|------------------------|------------------|----------------------|------------------|
| 430 | 8 | 600 | 2.16 | 0.26 | 1.90 | 200 |
| 430 | 10 | 300 | 1.37 | 0.18 | 1.19 | 312 |
| 430 | 10 | 600 | 2.63 | 0.26 | 2.37 | 148 |
| 430 | 12 | 300 | 1.68 | 0.26 | 1.42 | 240 |

PIU PRESTRETCH FILMS - AUTOMATIC USE

| Width (mm) | Gauge (my) | Length (m) | Gross Roll Weight (kg) | Core Weight (kg) | Net Roll Weight (kg) | Rolls Per Pallet |
|------------|------------|------------|------------------------|------------------|----------------------|------------------|
| 430 | 8 | 1,500 | 5.52 | 0.77 | 4.75 | 36 |
| 430 | 8 | 3,000 | 10.26 | 0.77 | 9.49 | 22 |
| 430 | 10 | 1,500 | 6.70 | 0.77 | 5.93 | 36 |
| 430 | 10 | 3,000 | 12.64 | 0.77 | 11.87 | 22 |
| 430 | 12 | 1,500 | 7.89 | 0.77 | 7.12 | 36 |
| 430 | 12 | 3,000 | 15.01 | 0.77 | 14.24 | 22 |



Strapping Tools And Accessories



Manual Strapping Tools: These are appropriate for various kinds of usages and offered in two types as light/medium and heavy duty applications.



Battery Charged Strapping Tools: The battery charged strapping tools used in PET and PP strapping applications are user friendly, safe and have high tensioning capacity.



Plastic Edge Protectors: They are suitable for different types of strapping and can be produced in custom colors upon request.



Plastic Buckles: Plastic strapping buckles are designed to work with polypropylene strapping; there is no need for strapping tools!

